

# Swing Door


## ASSA ABLOY SW300

**ASSA ABLOY**  
Entrance Systems

### Slim Profile Surface Mounted Operator

Experience a safer  
and more open world

### Technical Data Sheet



The ASSA ABLOY SW300 automatic swing operator is a low profile operator intended for use in exterior or interior entryways, corridors and a variety of applications. The ASSA ABLOY SW300 heavy duty (HD) electro-mechanical operator is suitable for use on large heavy doors, yet adaptable enough to be used in low energy (LE) applications. The product is surface mounted, and can be used on either side of the door, for pull or push applications. It is suitable for single doors, double doors and double egress doors fitted with swing clear hinges, offset pivots or center pivots. The operator is connected to the door leaf with a range of different arm systems. The low profile, slim header provides an ideal solution in applications with limited space.


ASSA ABLOY SW300 is designed to offer continuous use, a high degree of safety and maximum performance over the lifetime of your entrance. The ASSA ABLOY SW300 ensures all-around safety and can be equipped with a full range of sensor products providing swing door safety that meets or exceeds ANSI A156.10 standard.

#### Operator Features and Performance


- Operator: electro-mechanical, non-handed operator, 24 volt, 5/16 hp motor
- ANSI Compliance: Field selectable full pedestrian usage (ANSI A156.10) and low energy (ANSI A156.19)
- Door Weight: up to 621 pounds (282 kg) per operator
- Door Size: up to 48" (consult for wider sizes)
- Manual Push Force: adjustable from 5 lbf – 15 lbf
- Hold Open Time: adjustable from 1.5 seconds to 30 seconds
- Wind Force Dampening: operator mechanically counteracts to wind forces, slowing down the opening or closing of the door
- Stack Pressure Compensation: operator counteracts to positive stack pressures, negative stack pressures, and sudden changes of stack pressures to maintain consistent door speeds
- Intelligent Trajectory Control: operator knows where the door should be at all times and adjusts torque accordingly. Dynamic braking helps cushion the door during opening to prevent going past 90 degrees, or during closing to prevent slamming.
- Extended Closing Torque (ECT): exclusive Extended Closing Torque (ECT) functionality provides extra torque in the last 10 degrees of closing, if needed, to close and latch the door. Speed remains constant so the door stays within ANSI standards.



- Latch Retry: if the door does not latch when closing, the SW300 will detect this condition and immediately open the door to 10 degrees and execute two attempts to latch the door.
- On-board timing sequencer
- On-board 12V or 24V transformer
- Low pass filter (i.e. "delay on make")
- Door position relay
- Kill input to close doors immediately
- Self-learning set-up – measures inertia and door weight
- Low Power Consumption (300 watts, 2.5 amp (max))



**Door Set-ups:**  
**Left: Single**  
**Below Left: Dual Egress Below**  
**Right: Simultaneous Pair**



Available door arms: push, pull, double acting

## Operation

- Automatic sensor activation (ANSI A156.10)
- Push plate activation (ANSI A156.19 or A156.10)
- Push and go feature allowing door to open automatically when operator senses movement of door (ANSI A156.19)
- Power assist open – provides easy to open push forces (ANSI A156.19)
- Internal, push to open, push to close (i.e., ratchet relay) (ANSI A156.19)
- Speed controlled Extended Closing Torque (ECT) to provide power assist close with on-board functionality to automatically adjust torque without increasing speed
- Loss of Power: the operator controls the door closing, preventing slamming of door
- Torque Limiting: if positive air pressure condition is removed, operator compensates accordingly and will not slam

## Electric Lock Management

- Lock monitoring prevents operator(s) from opening door(s) until release of electrified lock
- Operator pulls door closed before opening, unjamming electric latch hardware
- Sequenced operation between operators for pairs of doors allowing lock release and astragal coordination
- Electric Lock Output: selectable 12 VDC, maximum 1200 mA / 24 VDC, maximum 600 mA

## Sensor Monitoring


- Monitored Door Mounted Presence Sensors – upon detection of sensor failure, the operator will automatically revert to low energy mode
- Blanking Potentiometer: tells sensors on swing side of door when to shut off
- Torque Cancellation – Extended Closing Torque (ECT) is deactivated if signal is received from door mounted presence sensors of a possible obstruction

## Aesthetics


- Aesthetically pleasing, low profile appearance: 2.75" (70mm) high by 6.539" (166.1mm) deep
- Continuous header for full width of door
- Finishes: anodized, powder coat, Kynar, clad

## Configurations

- Surface Applied • Side Load



Push Side View



Pull Side View

## Authorities

- Fire Door Rated Operator
- Intertek certified to UL10C, NFPA 252, CAN/ULC S104
- Conforms to ANSI/CAN/UL 325
- Conforms to UL Std. 991
- IBC
- ANSI A156.10 / ANSI A156.19
- CAN/CSA-C22.2 NO 223-M91 and CAN/CSA-C22.2 NO 223-M92IBC

## Sensor Packages

- Sensor Packages as follows:

### ANSI A156.19

- Activation: push plates per your selection
- Safety devices: not required per ANSI. Optional door mounted presence sensors (DMPS) are available

### ANSI A156.10

- Activation: push plates per your selection (motion sensors or push plates)
- Choice of ASSA ABLOY i-Adapt™ door mounted presence sensor system:
  - A202 – ASSA ABLOY i-Adapt Premium – stand alone, adapted field, door mounted presence sensors (DMPS)
  - A102 – ASSA ABLOY i-Adapt Flex – overhead presence sensor (OPS) and one door mounted presence sensor (DMPS) per swing and non-swing side
  - A101 – ASSA ABLOY i-Adapt Flex - overhead presence sensor (OPS) and one door mounted presence sensor (DMPS) swing side
  - A100 – ASSA ABLOY i-Adapt Flex – Knowing Act applications – dual egress only – overhead presence sensor (OPS) and motion sensor secondary activation per ANSI A156.10

<b>Operator type</b>	Electro-mechanical
<b>Door width</b>	36" – 48" (914 – 1219mm)
<b>Door weight</b>	Max. 621 lb (282 kg)
<b>Power supply</b>	120 V AC+10/-15%, 50/60 hz
<b>Power consumption</b>	Max. 300W
<b>Auxiliary voltage</b>	24 V DC, max. 700 mA
<b>Internal control fuse</b>	2 x T 6, 3 AH 250 V
<b>Electro-mechanical</b>	Selectable: 12V DC, max.
<b>Locking device</b>	1200 mA / 24 V DC, max. 600 mA

<b>Door opening</b>	<b>Push arm:</b> 80°- 110°, with reveal 0" – 13 13/16" (0mm-349mm) <b>Pull arm:</b> 80°- 110°, with reveal -3/4" to 5 1/8" (-20mm to 130mm) <b>Double-acting arm:</b> 90° in both directions, with reveal 0" (0mm)
---------------------	--

<b>Opening time (0 – 80°)</b>	Variable between 2 – 12 seconds
<b>Closing time (90 – 100°)</b>	Variable between 4 – 12 seconds
<b>Hold open time</b>	1,5-30 seconds
<b>Ambient temperature</b>	-4°F to 113°F (-20 °C to +45 °C)
<b>Relative humidity</b>	Max. 95%
<b>Drive weight unit (non-condensing)</b>	16.7 lb (7.6 kg)
This product is to be installed internally or externally with suitable weather protection.	
<b>Class of protection</b>	IP 20.
<b>Complies with:</b> ANSI/BHMA A156.19, ANSI/BHMA A156.10, UL325, UL 991, UL 10C, CAN/CSA-C22.2, NO 223-M91, CAN/CSA-C22.2 NO 247-92.	